

# **Austell Public Works**

Stormwater Management Division 5000 Austell-Powder Springs Road • Suite 133 • Austell, Georgia 30106 Office: (770) 944-4325 • Fax: (678) 264-1522

# FLOODPLAIN DEVELOPMENT PERMIT APPLICATION

This is an application packet for a Floodplain Development Permit. Certain sections are to be completed by the Applicant, and certain sections are to be completed by the local Floodplain Administrator.

The National Flood Insurance Program provides flood insurance to individuals at much lower premiums than could otherwise be purchased through private insurers. In order for citizens to be eligible for the national flood insurance rates, the City of Austell is a member of the National Flood Insurance Program and meets and/or exceeds minimum floodplain standards, where applicable. This application packet is a tool to ensure that the minimum standards are met.

Flood insurance policies can be purchased from any local insurance agent at the national rate. Even though the policy may be issued as if it were coming from the insurance company you deal with, it is actually a federal National Flood Insurance Policy printed on the insurance agency's letterhead. The rates are determined by the flood risk zone in which you live and by the elevation of the lowest floor of your home, not by the insurance company, and should be the same regardless of which agent or agency sells you the insurance.

You may buy flood insurance for your own peace of mind, you may be required to buy it before a lending institution will make or refinance a loan, or you may not be buying flood insurance at all. Whatever the case, if the property which you propose to develop is located within a "Special Flood Hazard Area" on a flood map issued by the Federal Emergency Management Agency, you <u>MUST</u> obtain a Floodplain Development Permit prior to beginning the project. This is a requirement of the City of Austell Floodplain Management and Prevention Ordinance, and there are penalties for failing to do so.

Floodplain Development Permits are ONLY required for developments in areas designated as "Special Flood Hazard Areas" of FEMA-issued flood maps. Flood maps can be reviewed at our office, or online at the Federal Emergency Management Agency's website (www.FEMA.gov).

If you are proposing a development of any kind (constructing a new building, adding on to an existing building, clearing land, placing fill, grading land, mining, dredging, drilling, etc.) in a floodplain, you <u>MUST</u> submit Section I of this application for a Floodplain Development Permit to Austell Public Works. Depending upon the type of development you are proposing, additional forms *may* be required. For example, all new buildings in a Special Flood Hazard Area require an Elevation Certificate to document that the lowest floor of the building is elevated to a certain height relative to the anticipated flood crest of the "base flood" event. The Elevation Certificate and other forms are provided in Section III of this application packet, *but should only be completed if they are required by Austell Public Works for the proposed development*.

Typically, the Applicant completes Section I of this packet and submits the information to Austell Public Works. The Floodplain Management staff reviews the submission and determines whether or not additional information is needed. If it is, the reviewer will request the additional information from the Applicant. Once all required materials have been submitted, the reviewer will make a permitting decision and either issue or deny the requested Floodplain Development Permit. (Denied permits may be appealed per the provisions of the local Floodplain Management and Prevention Ordinance.)

The Applicant should understand that a Floodplain Development Permit is only a permit to complete the proposed development. It is a permit to, for example, build a house, construct a baseball field, install a drainage ditch or septic system or grade a parcel of land. Before the house can actually be occupied, or the developed land used, a Certificate of Compliance must be issued by Austell Public Works. An inspection will be conducted after the project is completed, or perhaps several inspections throughout the progress of the project, to make sure that the development is compliant with the requirements of the Floodplain Management and Prevention Ordinance. Once the Certificate of Compliance has been issued, the process has been completed.

#### INSTRUCTIONS FOR COMPLETION

#### SECTION I

#### General Information

Self-explanatory. Note the last two items under this heading.

#### **Owner Information**

List the contact information for the owner(s) of the property where development is proposed. All owners of the property must sign the application.

#### Applicant Information

If you are applying for this development permit, but are not the owner of the property, list your contact information here. If you are the property owner, leave this section blank.

#### Project Information

Check the appropriate box(es) beside the type of development that is being proposed. Note that some types of activity require the estimated cost of the proposed project to be disclosed so the Floodplain Administrator can determine whether or not the improvement is a "substantial improvement."

#### **Signature**

Print your name, sign your name, and date the application.

#### SECTION II

#### **Floodplain Information**

The Floodplain Administrator will determine - for the sole purpose of administering the Floodplain Management and Prevention Ordinance - the position of the proposed development relative to floodplains and floodways within the City of Austell. This determination is not binding at any lending institution or with any insurance agency, but is used to determine whether or not a Floodplain Development Permit and/or any other forms are required prior to commencing the proposed project.

Section II requires a map and panel number(s), a listing of the flood source for the proposed development, and contains a checklist of additional documents required for the Floodplain Administrator to make an informed permitting decision.

If any of the additional documentation is required, the Floodplain Administrator will notify the applicant, allow a reasonable length of time for submission of the documents, and then review all submissions to determine whether or not the permit will be issued.

#### SECTION III

#### Forms

Templates for forms that may be required are provided in this Section.

#### SECTION IV

#### Permit Determination

The Floodplain Administrator will indicate whether or not the proposed development is conformant with the requirements of the Floodplain Management and Prevention Ordinance, and whether or not the requested permit is issued. If the decision is to NOT issue the permit, the Floodplain Administrator will provide an explanation of the deficiencies to the Applicant.

#### SECTION V

#### Certificate of Compliance

The Floodplain Administrator will indicate the "as-built" lowest floor elevation for structural developments, list any inspections that have been performed, and issue the Certificate of Compliance to the Applicant if appropriate.



Stormwater Management Division 5000 Austell-Powder Springs Road • Suite 133 • Austell, Georgia 30106 Office: (770) 944-4325 • Fax: (770) 944-4335 **OFFICE USE ONLY** 

Date Received:

File Number: FDP-

## FLOODPLAIN DEVELOPMENT PERMIT APPLICATION

# **SECTION I: Applicant and Project Information**

# GENERAL INFORMATION

- 1. No work of any kind may begin in a floodplain area designated as A, A1-30, AE, AO, AH, or B until a floodplain development permit is issued.
- 2. The permit may be revoked if any false statements are made in this application.
- 3. If revoked, all work must cease until a permit is re-issued.
- 4. The development may not be used or occupied until a Certificate of Compliance is issued.
- 5. The permit will expire if no work is commenced within six months of the date of issue.
- 6. The permit will not be issued until any other necessary local, state or federal permits have been obtained.
- 7. By signing and submitting this application, the Applicant gives consent to the local Floodplain Administrator or his/her representative to make reasonable inspections prior to the issuance of a Certificate of Compliance.
- 8. By signing and submitting this application, the Applicant certifies that all statements contained in Section I of the application, and in any additional attachments submitted by the Applicant, are true and accurate.

#### OWNER INFORMATION

Property Owner(s):

Telephone Number:

Fax Number:

Mailing Address:

E-Mail address:

Signature(s) of property owner(s) listed above<sup>1</sup>

<sup>1</sup>Attached forms if there are additional property owners. This permit application will not be accepted without the signature of all property owners. The signature is an acknowledgement and consent to this Floodplain Development Permit application.

APPLICANT INFORM	IATION		
Applicant:		Notes:	
Telephone Number:			
Fax Number:			
Applicant Signature:			

#### SECTION I CONTINUED ON BACK

File Number: FDP
------------------

Project	Lot	Block
Address	Subdivision	
	Legal Description	Attach to this document
A. Structural development (Please check c	all that apply.)	
Type of Structure		
Residential (1 to 4 families)         Residential (More than 4 families)         Non-Residential         Elevated         Floodproofed         Combined Use (Residential an Manufactured (mobile) Home         Located within a Manufactured (mobile) Home	d Non-Residential ctured Home Park	
Type of Structural ActivityNew StructureAddition to Existing StructureAlteration of Existing StructurRelocation of Existing StructurDemolition of Existing StructurReplacement of Existing Structur	e <sup>2</sup> re <sup>2</sup> ire	
P. Other Development Activities		<sup>2</sup> Estimate Cost of Project
B. <u>Other Development Activities</u>	mustural Davidonment li	stad in Dart A)
Excavation (not related to a St Clearing	ructural Development if	sted in Part A.)
<ul> <li>Placement of Fill Material</li> <li>Grading</li> <li>Mining</li> <li>Drilling</li> <li>Dredging</li> <li>Watercourse Alteration</li> <li>Drainage Improvement (incluction)</li> <li>Individual Water or Sewer System</li> <li>Roadway or Bridge Construction</li> <li>Other Development Not Listed</li> </ul>	stem	<sup>2</sup> If the value of an addition or alteration to a Structure equals or exceeds 50% of the value of the structure before the addition or alteration, the entire structure must be treated as a substantially improved structure. A relocated structure must be treated as new construction.
SIGNATURE		
I certify that to the best of my knowledge t	he information containe	d in this application is true and accurate.
PRINTED NAME	SIGNAT	URE DATE

File Number: FDP-

SE	CTION II: (To be completed by Floodplain Administrator)
FL	OOD INFORMATION
1.	The proposed development is located on FIRM map panel: (number and suffix)
2.	FIRM Date: March 4, 2013
3.	The proposed development is located in Zone: (A, A1-30, AE, AO, AH, B, C, D, or X)
4.	Is the proposed development located in either of the following zones? A, A1-30, AE, AO, AH, B, or shaded X
	YES NO If NO, no permit floodplain development is required.
5.	If the proposed development is located in Zone B or shaded Zone X, a floodplain development permit is only
	required if the Development is a "critical facility" as defined in the Flood Damage Prevention Ordinance.
	Otherwise, no floodplain development permit is required in Zone B or shaded Zone X.
6.	If the proposed development is located within either Zone A1-30 or Zone AE, is it also located within a
	"regulatory floodway"?
7.	If YES, a <b>No Rise Certificate</b> is necessary before proceeding.
8.	If NO, continue.
	If the proposed development is located within Zones A, A1-30, AE, AO, AH, <u>B or shaded X (critical facilities only)</u> , apply the criteria of the Floodplain Management and Prevention Ordinance to minimize flood damages to the proposed Development and to adjacent properties as well.
	For structures, the provisions of the ordinance specify that the lowest floor, including utilities, be elevatedabove the base flood elevation. Therefore, it is necessary that the following information be provided:
1.	Site Base Flood Elevation: feet above mean sea level (MSL)
2.	Vertical datum used in the Flood Insurance Study, on flood maps and in surveys is
3.	Source of the base flood elevation (BFE) FIRM (flood map)
	Flood Insurance Study Profile Number:
	Other sources of the BFE (specify):
4.	Proposed lowest floor elevation (including utilities): feet above MSL
	(This elevation must be greater than the BFE. For non-residential structures, floodproofing may be used for protection. See ordinance for details.)
	The following documents may be required.Check applicable.
	Maps and plans of the development
	<ul> <li>An Elevation Certificate<sup>3</sup> – required for all structures</li> <li>A Floodproofing Certificate<sup>3</sup> – required if floodproofing a non-residential structure</li> </ul>
	$\square$ A No-Rise Certificate <sup>3</sup> – if the proposed development is in a "regulatory floodway"
	An elevation study showing BFEs on developments exceeding 50 lots or 5 acres in Zone A
	A copy of <b>Wetlands Permit</b> from the U.S. Army Corps of Engineers if required; and other local, state, federal permits. Other permits:
	<sup>3</sup> Certificates require completion by a Professional Land Surveyor or Registered Professional Engineer, as indicated.

File Number: FDP-

# SECTION III : (Forms which may be required by the Floodplain Administrator)

# **ELEVATION CERTIFICATE**

Attached. This is required for all projects, per lot.

# FLOODPROOFING CERTIFICATE

Attached. Submit only if required to do so by the Floodplain Administrator.

# **NO-RISE CERTIFICATE**

Attached. Submit if only applicable for this project.

# NATIONAL FLOOD INSURANCE PROGRAM ENGINEERING "NO-RISE" CERTIFICATE

SITE INFORMATI	ON					
Community:	City of Austell, G	eorgia	County:	Cobb	Douglas	
			Date:			
Applicant:			Engineer:			
Address:			Address:			
Telephone:			Telephone:			
E-Mail Address:			E-Mail Address:			
Subdivision:			Lot and Block:			
Project Address:			Legal Description:	Attach	n as separate do	cument
PROJECT INFORM	ATION					
Description of Dev	velopment:					
Principal Use of Pr	remises:					
FLOOD INSURAN	CE RATE MAP (F	IRM) INFOR	MATION			
Map(s) and Panel(s						
		Jarob 1 2012				
Effective Date of N		March 4, 2013				
Base Flood Elevati	on on FIRM:					
Name of Flooding	Source:					
CERTIFICATION						
This is to certify that the attached engineer levels within the City	ring data supports th	he fact the pro	posed development	would not	0	
					SEAL	1
CERTIFII	ERS NAME	LICI	ENSE NUMBER			
COMPA	NY NAME	_				
SIGN	ATURE		DATE			
TI	TLE	-				J

# **OFFICE USE ONLY**

AUSTELL PUBLIC WORKS FLOOD DEVELOPMENT PERMIT Date Issued:

File Number: FDP-

SECTION IV: (To be completed by the Floodplain Administrator)				
PERMIT DETERMINATION				
I have determined that the proposed development				
<ul> <li>IS</li> <li>IS NOT (non-conformances to be described in a separate document)</li> <li>in conformance with the City of Austel Flood Management and Prevention Ordinance.</li> </ul>				
The Floodplain Development Permit				
<ul> <li>IS</li> <li>IS NOT (reasons for denial to be described in a separate document)</li> </ul>				
issued, subject to any conditions attached to and made part of this permit.				
Floodplain Administrator Date				
The applicant is reminded that this document is a development permit only. An inspection must be performed and a Compliance Certificate must be issued before the development can be occupied or used.				

## CITY OF AUSTELL CERTIFICATE OF COMPLIANCE

### SECTION V: CERTIFICATE OF COMPLIANCE

#### "AS-BUILT" ELEVATION (to be completed by the applicant after construction)

The following information must be provided for structures that are part of this application. This section must be completed by a Professional Land Surveyor or a Professional Engineer (or attach a certification to this application).

- (1) The Actual ("As-Built") elevation of the top of the lowest floor, including the basement, is \_\_\_\_\_\_\_. Feet above MSL (vertical datum: \_\_\_\_\_\_).
- (2) The Actual ("As-Built") elevation of floodproofing protection is \_\_\_\_\_\_ Feet above MSL (vertical datum: \_\_\_\_\_)

# **COMPLIANCE ACTION (to be completed by the Local Floodplain Administrator)**

The Floodplain Administrator will complete this section, as applicable, based on inspection of the development to ensure compliance with the Floodplain Management and Prevention Ordinance.

Inspections:	Date:	By:	Deficiencies?	Yes	🗌 No
	Date:	By:	Deficiencies?	Yes	🗌 No
	Date:	By:	Deficiencies?	Yes	🗌 No
	Date:	By:	Deficiencies?	Yes	🗌 No
	Date:	By:	Deficiencies?	Yes	🗌 No

#### **CERTIFICATE OF COMPLIANCE (to be completed by the Local Floodplain Administrator)**

Certificate of Compliance issued.

Floodplain Administrator

Date

This Certificate of Compliance indicates that structures may now be occupied and nonstructural developments may be utilized.

#### **OFFICE USE ONLY**

Date Issued: FDP-

File Number:





NATIONAL FLOOD INSURANCE PROGRAM

# **ELEVATION CERTIFICATE**

# AND

INSTRUCTIONS

**2012 EDITION** 

# National Flood Insurance Program **ELEVATION CERTIFICATE**

#### **Paperwork Reduction Act Notice**

Public reporting burden for this data collection is estimated to average 3.75 hours per response. The burden estimate includes the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and submitting this form. You are not required to respond to this collection of information unless a valid OMB control number is displayed on this form. Send comments regarding the accuracy of the burden estimate and any suggestions for reducing the burden to: Information Collections Management, Department of Homeland Security, Federal Emergency Management Agency, 1800 South Bell Street, Arlington, VA 20598-3005, Paperwork Reduction Project (1660-0008). **NOTE: Do not send your completed form to this address.** 

#### **Privacy Act Statement**

Authority: Title 44 CFR § 61.7 and 61.8.

**Principal Purpose(s):** This information is being collected for the primary purpose of estimating the risk premium rates necessary to provide flood insurance for new or substantially improved structures in designated Special Flood Hazard Areas.

**Routine Use(s):** The information on this form may be disclosed as generally permitted under 5 U.S.C. § 552a(b) of the Privacy Act of 1974, as amended. This includes using this information as necessary and authorized by the routine uses published in DHS/FEMA-003 – National Flood Insurance Program Files System or Records Notice 73 Fed. Reg. 77747 (December 19, 2008); DHS/FEMA/NFIP/ LOMA-1 – National Flood Insurance Program (NFIP) Letter of Map Amendment (LOMA) System of Records Notice 71 Fed. Reg. 7990 (February 15, 2006); and upon written request, written consent, by agreement, or as required by law.

**Disclosure:** The disclosure of information on this form is voluntary; however, failure to provide the information requested may result in the inability to obtain flood insurance through the National Flood Insurance Program or the applicant may be subject to higher premium rates for flood insurance. Information will only be released as permitted by law.

#### **Purpose of the Elevation Certificate**

The Elevation Certificate is an important administrative tool of the National Flood Insurance Program (NFIP). It is to be used to provide elevation information necessary to ensure compliance with community floodplain management ordinances, to determine the proper insurance premium rate, and to support a request for a Letter of Map Amendment (LOMA) or Letter of Map Revision based on fill (LOMR-F).

The Elevation Certificate is required in order to properly rate Post-FIRM buildings, which are buildings constructed after publication of the Flood Insurance Rate Map (FIRM), located in flood insurance Zones A1–A30, AE, AH, A (with BFE), VE, V1–V30, V (with BFE), AR, AR/A, AR/AE, AR/A1–A30, AR/AH, and AR/A0. The Elevation Certificate is not required for Pre-FIRM buildings unless the building is being rated under the optional Post-FIRM flood insurance rules.

As part of the agreement for making flood insurance available in a community, the NFIP requires the community to adopt floodplain management regulations that specify minimum requirements for reducing flood losses. One such requirement is for the community to obtain the elevation of the lowest floor (including basement) of all new and substantially improved buildings, and maintain a record of such information. The Elevation Certificate provides a way for a community to document compliance with the community's floodplain management ordinance.

Use of this certificate does not provide a waiver of the flood insurance purchase requirement. Only a LOMA or LOMR-F from the Federal Emergency Management Agency (FEMA) can amend the FIRM and remove the Federal mandate for a lending institution to require the purchase of flood insurance. However, the lending institution has the option of requiring flood insurance even if a LOMA/LOMR-F has been issued by FEMA. The Elevation Certificate may be used to support a LOMA or LOMR-F request. Lowest floor and lowest adjacent grade elevations certified by a surveyor or engineer will be required if the certificate is used to support a LOMA or LOMR-F request. A LOMA or LOMR-F request must be submitted with either a completed FEMA MT-EZ or MT-1 package, whichever is appropriate.

This certificate is used only to certify building elevations. A separate certificate is required for floodproofing. Under the NFIP, nonresidential buildings can be floodproofed up to or above the Base Flood Elevation (BFE). A floodproofed building is a building that has been designed and constructed to be watertight (substantially impermeable to floodwaters) below the BFE. Floodproofing of residential buildings is not permitted under the NFIP unless FEMA has granted the community an exception for residential floodproofed basements. The community must adopt standards for design and construction of floodproofed basements before FEMA will grant a basement exception. For both floodproofed non-residential buildings and residential floodproofed basements in communities that have been granted an exception by FEMA, a floodproofing certificate is required.

Additional guidance can be found in FEMA Publication 467-1, Floodplain Management Bulletin: Elevation Certificate, available on FEMA's website at <a href="http://www.fema.gov/library/viewRecord.do?id=1727">http://www.fema.gov/library/viewRecord.do?id=1727</a>.

#### U.S. DEPARTMENT OF HOMELAND SECURITY FEDERAL EMERGENCY MANAGEMENT AGENCY

National Flood Insurance Program

**ELEVATION CERTIFICATE IMPORTANT:** Follow the instructions on pages 1–9.

OMB No. 1660-0008 Expiration Date: July 31, 2015

SECTI	OR INSURANCE COMPANY USE				
A1. Building Owner's Name Policy			blicy Number:		
A2. Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No.			ompany NAIC Number:		
City	State	)	ZIF	? Code	
A3. Property Description (Lot and Block Numbers, Tax Parcel	Number, Legal Descriptio	n, etc.)			
<ul> <li>A4. Building Use (e.g., Residential, Non-Residential, Addition</li> <li>A5. Latitude/Longitude: Lat</li> <li>A6. Attach at least 2 photographs of the building if the Certif</li> <li>A7. Building Diagram Number</li> <li>A8. For a building with a crawlspace or enclosure(s):</li> </ul>	Long.	ain flood insura	Horizontal Da	ntum: NAD 1927 NAD 1983	
<ul> <li>a) Square footage of crawlspace or enclosure(s)</li> <li>b) Number of permanent flood openings in the crawlspace or enclosure(s) within 1.0 foot above adjacent grade</li> <li>c) Total net area of flood openings in A8.b</li> <li>d) Engineered flood openings?  </li> </ul>	ce sq ft sq in	b) Numbe within 2 c) Total ne	1.0 foot above a et area of flood o	flood openings in the attached garage	
SECTION B – FLOOD	INSURANCE RATE N	IAP (FIRM) I	NFORMATION		
B1. NFIP Community Name & Community Number	B2. County Nam	. ,		B3. State	
B4. Map/Panel Number B5. Suffix B6. FIRM Index D	Date B7. FIRM Panel I Revised Date		. Flood Zone(s)	B9. Base Flood Elevation(s) (Zone A0, use base flood depth)	
B10. Indicate the source of the Base Flood Elevation (BFE) dat				·	
	■ NGVD 1929 ■ NAV stem (CBRS) area or Othe	D 1988 🗌	Other/Source: _		
SECTION C – BUILDING	G ELEVATION INFORM	IATION (SUR	VEY REQUIRE	ED)	
*A new Elevation Certificate will be required when constr	<ul> <li>C1. Building elevations are based on: Construction Drawings* Building Under Construction* Finished Construction * A new Elevation Certificate will be required when construction of the building is complete.</li> <li>C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V1–V30, V (with BFE), AR, AR/A, AR/AE, AR/A1–A30, AR/AH, AR/A0. Complete Items</li> </ul>				
C2.a–h below according to the building diagram specified		-	eters.		
Benchmark Utilized: Indicate elevation datum used for the elevations in items Datum used for building elevations must be the same as	a) through h) below.	Datum: NGVD 1929   []		 ] Other/Source: asurement used.	
a) Top of bottom floor (including basement, crawlspace,	or enclosure floor)		🗌 feet	meters	
b) Top of the next higher floor			🗌 feet	meters	
c) Bottom of the lowest horizontal structural member (V	Zones only)	·	🗌 feet	meters	
d) Attached garage (top of slab)		·	🗌 feet	meters	
<ul> <li>e) Lowest elevation of machinery or equipment servicing (Describe type of equipment and location in Comment</li> </ul>	ts)		🗌 feet	meters	
f) Lowest adjacent (finished) grade next to building (LAG	)	·	feet	meters	
<ul> <li>g) Highest adjacent (finished) grade next to building (HAG)</li> <li>h) Lowest adjacent grade at lowest elevation of deck or stairs, including</li> <li>structural support</li> </ul>					
SECTION D – SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION					
This certification is to be signed and sealed by a land surveyor, engineer, or architect authorized by law to certify elevation information. I certify that the information on this Certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.					
□ Check here if comments are provided on back of form.       Were latitude and longitude in Section A provided by a         □ Check here if attachments.       licensed land surveyor?       Yes       No					
Certifier's Name License Number PLACE SEAL					
Title	Company Name			HERE	
Address	City	State	ZIP Code		
Signature	Date	Telephone			

#### **ELEVATION CERTIFICATE**, page 2

IMPORTANT: In these spaces, copy the correspondence of the corresp			FOR IN	ISURANCE COMPANY USE
Building Street Address (including Apt., Unit, Suite	e, and/or Bldg. No.) or PO.	Route and Box No.	Policy N	Number:
City	State	ZIP Code	Compa	ny NAIC Number:
SECTION D – SUR	VEYOR, ENGINEER, OI	R ARCHITECT C		UED)
Copy both sides of this Elevation Certificate for (1	) community official, (2) in	surance agent/com	pany, and (3) building owner.	
Comments				
Signature		Date		
SECTION E – BUILDING ELEVATION I	NFORMATION (SURVE	Y NOT REQUIRE	D) FOR ZONE AO AND Z	ZONE A (WITHOUT BFE)
For Zones AO and A (without BFE), complete Items For Items E1–E4, use natural grade, if available. O				st, complete Sections A, B,and C.
E1. Provide elevation information for the following				or below the highest adjacent
grade (HAG) and the lowest adjacent grade (L				
a) Top of bottom floor (including basement, cra	awlspace, or enclosure) is	·		above or below the HAG.
b) Top of bottom floor (including basement, cra	awlspace, or enclosure) is		feet $\Box$ meters $\Box$	above or $\Box$ below the LAG.
E2. For Building Diagrams 6–9 with permanent flo	od openings provided in Se	ection A Items 8 an	d/or 9 (see pages 8–9 of Ins	structions),
the next higher floor (elevation C2.b in the dia	grams) of the building is			above or below the HAG.
E3. Attached garage (top of slab) is			. feet meters	above or 🗌 below the HAG.
E4. Top of platform of machinery and/or equipment	nt servicing the building is	·	. 🗌 feet 🗌 meters 🗌	above or $\Box$ below the HAG.
E5. Zone AO only: If no flood depth number is avai ordinance? Yes No Unknown. Th	lable, is the top of the bot ne local official must certify			unity's floodplain management
SECTION F – PRO	PERTY OWNER (OR O	WNER'S REPRE	SENTATIVE) CERTIFICA	TION
The property owner or owner's authorized represe Zone AO must sign here. The statements in Section				ued or community-issued BFE) or
Property Owner or Owner's Authorized Representa	tive's Name			
Address		City	State	ZIP Code
Signature		Date	Telephone	
Comments				
				_  Check here if attachments.
	CTION G – COMMUNIT		· · · · · ·	
The local official who is authorized by law or ordinar G of this Elevation Certificate. Complete the applica	nce to administer the comm able item(s) and sign below.	unity's floodplain m Check the measure	anagement ordinance can cor ement used in Items G8–G10.	nplete Sections A, B, C (or E), and In Puerto Rico only, enter meters.
G1. The information in Section C was taken who is authorized by law to certify elevated				
G2. A community official completed Section E	for a building located in Z	one A (without a FE	MA-issued or community-issu	ued BFE) or Zone AO.
G3. 🗌 The following information (Items G4–G10	D) is provided for commun	ity floodplain mana	gement purposes.	
G4. Permit Number G5	5. Date Permit Issued	6	. Date Certificate Of Complia	ance/Occupancy Issued
G7. This permit has been issued for: $\Box$ New	Construction 🗌 Substa	antial Improvement		
G8. Elevation of as-built lowest floor (including ba	asement) of the building:	·	🗌 feet 🗌 meters Da	atum
G9. BFE or (in Zone AO) depth of flooding at the	ouilding site:	·		itum
G10.Community's design flood elevation:		·	☐ feet ☐ meters Da	itum
Local Official's Name		Title		
Community Name		Telephone		

------

Signature

Comments

\_ 🗌 Check here if attachments.

Date

#### **BUILDING PHOTOGRAPHS**

See Instructions for Item A6.

IMPORTANT: In these spaces, copy the	FOR INSURANCE COMPANY USE	
Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No.		Policy Number:
City	State ZIP Code	Company NAIC Number:

If using the Elevation Certificate to obtain NFIP flood insurance, affix at least 2 building photographs below according to the instructions for Item A6. Identify all photographs with date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." When applicable, photographs must show the foundation with representative examples of the flood openings or vents, as indicated in Section A8. If submitting more photographs than will fit on this page, use the Continuation Page.

#### **BUILDING PHOTOGRAPHS**

Continuation Page

IMPORTANT: In these spaces, copy t	FOR INSURANCE COMPANY USE	
Building Street Address (including Apt	Policy Number:	
City	State ZIP Code	Company NAIC Number:

If submitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." When applicable, photographs must show the foundation with representative examples of the flood openings or vents, as indicated in Section A8.

# Instructions for Completing the Elevation Certificate

The Elevation Certificate is to be completed by a land surveyor, engineer, or architect who is authorized by law to certify elevation information information is required for Zones A1–A30, AE, AH, A (with BFE), VE, V1–V30, V (with BFE), AR, AR/A, AR/AE, AR/A1–A30, AR/AH, or AR/AO. Community officials who are authorized by law or ordinance to provide floodplain management information may also complete this form. For Zones AO and A (without BFE), a community official, a property owner, or an owner's representative may provide information on this certificate, unless the elevations are intended for use in supporting a request for a LOMA or LOMR-F. Certified elevations must be included if the purpose of completing the Elevation Certificate is to obtain a LOMA or LOMR-F.

The property owner, the owner's representative, or local official who is authorized by law to administer the community floodplain ordinance can complete Section A and Section B. The partially completed form can then be given to the land surveyor, engineer, or architect to complete Section C. The land surveyor, engineer, or architect should verify the information provided by the property owner or owner's representative to ensure that this certificate is complete.

In Puerto Rico only, elevations for building information and flood hazard information may be entered in meters.

#### SECTION A – PROPERTY INFORMATION

**Items A1–A4.** This section identifies the building, its location, and its owner. Enter the name(s) of the building owner(s), the building's complete street address, and the lot and block numbers. If the building's address is different from the owner's address, enter the address of the building being certified. If the address is a rural route or a Post Office box number, enter the lot and block numbers, the tax parcel number, the legal description, or an abbreviated location description based on distance and direction from a fixed point of reference. For the purposes of this certificate, "building" means both a building and a manufactured (mobile) home.

A map may be attached to this certificate to show the location of the building on the property. A tax map, FIRM, or detailed community map is appropriate. If no map is available, provide a sketch of the property location, and the location of the building on the property. Include appropriate landmarks such as nearby roads, intersections, and bodies of water. For building use, indicate whether the building is residential, non-residential, an addition to an existing residential or non-residential building, an accessory building (e.g., garage), or other type of structure. Use the Comments area of the appropriate section if needed, or attach additional comments.

**Item A5.** Provide latitude and longitude coordinates for the center of the front of the building. Use either decimal degrees (e.g., 39.5043°, -110.7585°) or degrees, minutes, seconds (e.g., 39° 30' 15.5", -110° 45' 30.7") format. If decimal degrees are used, provide coordinates to at least 4 decimal places or better. When using degrees, minutes, seconds, provide seconds to at least 1 decimal place or better. The latitude and longitude coordinates must be accurate within 66 feet. When the latitude and longitude are provided by a surveyor, check the "Yes" box in Section D and indicate the method used to determine the latitude and longitude in the Comments area of Section D. If the Elevation Certificate is being certified by other than a licensed surveyor, engineer, or architect, this information is not required. Provide the type of datum used to obtain the latitude and longitude. FEMA prefers the use of NAD 1983.

**Item A6.** If the Elevation Certificate is being used to obtain flood insurance through the NFIP, the certifier must provide at least 2 photographs showing the front and rear of the building taken within 90 days from the date of certification. The photographs must be taken with views confirming the building description and diagram number provided in Section A. To the extent possible, these photographs should show the entire building including foundation. If the building has split-level or multi-level areas, provide at least 2 additional photographs showing side views of the building. In addition, when applicable, provide a photograph of the foundation showing a representative example of the flood openings or vents. All photographs must be in color and measure at least 3" × 3". Digital photographs are acceptable.

**Item A7.** Select the diagram on pages 7–9 that best represents the building. Then enter the diagram number and use the diagram to identify and determine the appropriate elevations requested in Items C2.a–h. If you are unsure of the correct diagram, select the diagram that most closely resembles the building being certified.

**Item A8.a** Provide the square footage of the crawlspace or enclosure(s) below the lowest elevated floor of an elevated building with or without permanent flood openings. Take the measurement from the outside of the crawlspace or enclosure(s). Examples of elevated buildings constructed with crawlspace and enclosure(s) are shown in Diagrams 6–9 on pages 8–9. Diagram 2, 4, or 9 should be used for a building constructed with a crawlspace floor that is below the exterior grade on all sides.

**Items A8.b**–d Enter in Item A8.b the number of permanent flood openings in the crawlspace or enclosure(s) that are no higher than 1.0 foot above the higher of the exterior or interior grade or floor immediately below the opening. (A permanent flood opening is a flood vent or other opening that allows the free passage of water automatically in both directions without human intervention.) If the interior grade elevation is used, note this in the Comments area of Section D. Estimate the total net area of all such permanent flood openings in square inches, excluding any bars, louvers, or other covers of the permanent flood openings and enter the total in Item A8.c. If the net area cannot be reasonably estimated, provide the size of the flood openings. Indicate in Item A8.d whether the flood openings are engineered. If applicable, attach a copy of the Individual Engineered Flood Openings Certification or an Evaluation Report issued by the International Code Council Evaluation Service (ICC ES), if you have it. If the crawlspace or enclosure(s) have no permanent flood openings, or if the openings are not within 1.0 foot above adjacent grade, enter "0" (zero) in Items A8.b–c.

**Item A9.a** Provide the square footage of the attached garage with or without permanent flood openings. Take the measurement from the outside of the garage.

**Items A9.b**–d Enter in Item A9.b the number of permanent flood openings in the attached garage that are no higher than 1.0 foot above the higher of the exterior or interior grade or floor immediately below the opening. (A permanent flood opening is a flood vent or other opening that allows the free passage of water automatically in both directions without human intervention.) If the interior grade elevation is used, note this in the Comments area of Section D. This includes any openings that are in the garage door that are no higher than 1.0 foot above the adjacent grade. Estimate the total net area of all such permanent flood openings in square inches and enter the total in Item A9.c. If the net area cannot be reasonably estimated, provide the size of the flood openings without consideration of any covers and indicate in the Comments area the type of cover that exists in the flood openings. Indicate in Item A9.d whether the flood openings are engineered. If applicable, attach a copy of the Individual Engineered Flood Openings Certification or an Evaluation Report issued by the International Code Council Evaluation Service (ICC ES), if you have it. If the garage has no permanent flood openings, or if the openings are not within 1.0 foot above adjacent grade, enter "0" (zero) in Items A9.b–c.

#### SECTION B - FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Complete the Elevation Certificate on the basis of the FIRM in effect at the time of the certification.

The information for Section B is obtained by reviewing the FIRM panel that includes the building's location. Information about the current FIRM is available from the Federal Emergency Management Agency (FEMA) by calling 1-800-358-9616. If a Letter of Map Amendment (LOMA) or Letter of Map Revision (LOMR-F) has been issued by FEMA, please provide the letter date and case number in the Comments area of Section D or Section G, as appropriate.

For a building in an area that has been annexed by one community but is shown on another community's FIRM, enter the community name and 6-digit number of the annexing community in Item B1, the name of the county or new county, if necessary, in Item B2, and the FIRM index date for the annexing community in Item B6. Enter information from the actual FIRM panel that shows the building location, even if it is the FIRM for the previous jurisdiction, in Items B4, B5, B7, B8, and B9.

If the map in effect at the time of the building's construction was other than the current FIRM, and you have the past map information pertaining to the building, provide the information in the Comments area of Section D.

**Item B1.** NFIP Community Name & Community Number. Enter the complete name of the community in which the building is located and the associated 6-digit community number. For a newly incorporated community, use the name and 6-digit number of the new community. Under the NFIP, a "community" is any State or area or political subdivision thereof, or any Indian tribe or authorized native organization, that has authority to adopt and enforce floodplain management regulations for the areas within its jurisdiction. To determine the current community number, see the NFIP Community Status Book, available on FEMA's web site at http://www.fema.gov/fema/csb.shtm, or call 1-800-358-9616.

**Item B2.** County Name. Enter the name of the county or counties in which the community is located. For an unincorporated area of a county, enter "unincorporated area." For an independent city, enter "independent city."

Item B3. State. Enter the 2-letter state abbreviation (for example, VA, TX, CA).

**Items B4–B5.** Map/Panel Number and Suffix. Enter the 10-character "Map Number" or "Community Panel Number" shown on the FIRM where the building or manufactured (mobile) home is located. For maps in a county-wide format, the sixth character of the "Map Number" is the letter "C" followed by a 4-digit map number. For maps not in a county-wide format, enter the "Community Panel Number" shown on the FIRM.

Item B6. FIRM Index Date. Enter the effective date or the map revised date shown on the FIRM Index.

**Item B7.** FIRM Panel Effective/Revised Date. Enter the map effective date or the map revised date shown on the FIRM panel. This will be the latest of all dates shown on the map. The current FIRM panel effective date can be determined by calling 1-800-358-9616.

**Item B8.** Flood Zone(s). Enter the flood zone, or flood zones, in which the building is located. All flood zones containing the letter "A" or "V" are considered Special Flood Hazard Areas. The flood zones are A, AE, A1–A30, V, VE, V1–V30, AH, AO, AR, AR/A, AR/AE, AR/A1–A30, AR/AH, and AR/AO. Each flood zone is defined in the legend of the FIRM panel on which it appears.

**Item B9.** Base Flood Elevation(s). Using the appropriate Flood Insurance Study (FIS) Profile, Floodway Data Table, or FIRM panel, locate the property and enter the BFE (or base flood depth) of the building site. If the building is located in more than 1 flood zone in Item B8, list all appropriate BFEs in Item B9. BFEs are shown on a FIRM or FIS Profile for Zones A1–A30, AE, AH, V1–V30, VE, AR, AR/A, AR/AE, AR/A1–A30, AR/AH, and AR/AO; flood depth numbers are shown for Zone AO. Use the AR BFE if the building is located in any of Zones AR/A, AR/AE, AR/A1 A30, AR/AH, or AR/AO. In A or V zones where BFEs are not provided on the FIRM, BFEs may be available from another source. For example, the community may have established BFEs or obtained BFE data from other sources for the building site. For subdivisions and other developments of more than 50 lots or 5 acres, establishment of BFEs is required by the community's floodplain management ordinance. If a BFE is obtained from another source, enter the BFE in Item B9. In an A Zone where BFEs are not available, complete Section E and enter N/A for Section B, Item B9. Enter the BFE to the nearest tenth of a foot (nearest tenth of a meter, in Puerto Rico).

**Item B10.** Indicate the source of the BFE that you entered in Item B9. If the BFE is from a source other than FIS Profile, FIRM, or community, describe the source of the BFE.

**Item B11.** Indicate the elevation datum to which the elevations on the applicable FIRM are referenced as shown on the map legend. The vertical datum is shown in the Map Legend and/or the Notes to Users on the FIRM.

**Item B12.** Indicate whether the building is located in a Coastal Barrier Resources System (CBRS) area or Otherwise Protected Area (OPA). (OPAs are portions of coastal barriers that are owned by Federal, State, or local governments or by certain non-profit organizations and used primarily for natural resources protection.) Federal flood insurance is prohibited in designated CBRS areas or OPAs for buildings or manufactured (mobile) homes built or substantially improved after the date of the CBRS or OPA designation. For the first CBRS designations, that date is October 1, 1983. Information about CBRS areas and OPAs may be obtained on the FEMA web site at <a href="http://www.fema.gov/business/nfip/cbrs/cbrs.shtm">http://www.fema.gov/business/nfip/cbrs/cbrs.shtm</a>.

#### SECTION C - BUILDING ELEVATION INFORMATION (SURVEY REQUIRED)

Complete Section C if the building is located in any of Zones A1–A30, AE, AH, A (with BFE), VE, V1–V30, V (with BFE), AR, AR/A, AR/AE, AR/A1–A30, AR/AH, or AR/AO, or if this certificate is being used to support a request for a LOMA or LOMR-F. If the building is located in Zone AO or Zone A (without BFE), complete Section E instead. To ensure that all required elevations are obtained, it may be necessary to enter the building (for instance, if the building has a basement or sunken living room, split-level construction, or machinery and equipment).

Surveyors may not be able to gain access to some crawlspaces to shoot the elevation of the crawlspace floor. If access to the crawlspace is limited or cannot be gained, follow one of these procedures.

- Use a yardstick or tape measure to measure the height from the floor of the crawlspace to the "next higher floor," and then subtract the crawlspace height from the elevation of the "next higher floor." If there is no access to the crawlspace, use the exterior grade next to the structure to measure the height of the crawlspace to the "next higher floor."
- Contact the local floodplain administrator of the community in which the building is located. The community may have documentation of the elevation of the crawlspace floor as part of the permit issued for the building.
- If the property owner has documentation or knows the height of the crawlspace floor to the next higher floor, try to verify this by looking inside the crawlspace through any openings or vents.

In all 3 cases, provide the elevation in the Comments area of Section D on the back of the form and a brief description of how the elevation was obtained.


**Item C1.** Indicate whether the elevations to be entered in this section are based on construction drawings, a building under construction, or finished construction. For either of the first 2 choices, a post-construction Elevation Certificate will be required when construction is complete. If the building is under construction, include only those elevations that can be surveyed in Items C2.a–h. Use the Comments area of Section D to provide elevations obtained from the construction plans or drawings. Select "Finished Construction" only when all machinery and/or equipment such as furnaces, hot water heaters, heat pumps, air conditioners, and elevators and their associated equipment have been installed and the grading around the building is completed.

**Item C2.** A field survey is required for Items C2.a–h. Most control networks will assign a unique identifier for each benchmark. For example, the National Geodetic Survey uses the Permanent Identifier (PID). For the benchmark utilized, provide the PID or other unique identifier assigned by the maintainer of the benchmark. For GPS survey, indicate the benchmark used for the base station, the Continuously Operating Reference Stations (CORS) sites used for an On-line Positioning User Service (OPUS) solution (also attach the OPUS report), or the name of the Real Time Network used.

Also provide the vertical datum for the benchmark elevation. All elevations for the certificate, including the elevations for Items C2.a–h, must use the same datum on which the BFE is based. Show the conversion from the field survey datum used if it differs from the datum used for the BFE entered in Item B9 and indicate the conversion software used. Show the datum conversion, if applicable, in the Comments area of Section D.

For property experiencing ground subsidence, the most recent reference mark elevations must be used for determining building elevations. However, when subsidence is involved, the BFE should not be adjusted. Enter elevations in Items C2.a—h to the nearest tenth of a foot (nearest tenth of a meter, in Puerto Rico).

**Items C2.a–d** Enter the building elevations (excluding the attached garage) indicated by the selected building diagram (Item A7) in Items C2.a–c. If there is an attached garage, enter the elevation for top of attached garage slab in Item C2.d. (Because elevation for top of attached garage slab is self-explanatory, attached garages are not illustrated in the diagrams.) If the building is located in a V zone on the FIRM, complete Item C2.c. If the flood zone cannot be determined, enter elevations for all of Items C2.a–h. For buildings in A zones, elevations a, b, d, and e should be measured at the top of the floor. For buildings in V zones, elevation c must be measured at the bottom of the lowest horizontal structural member of the floor (see drawing below). For buildings



elevated on a crawlspace, Diagrams 8 and 9, enter the elevation of the top of the crawlspace floor in Item C2.a, whether or not the crawlspace has permanent flood openings (flood vents). If any item does not apply to the building, enter "N/A" for not applicable.

**Item C2.e** Enter the lowest platform elevation of at least 1 of the following machinery and equipment items: elevators and their associated equipment, furnaces, hot water heaters, heat pumps, and air conditioners in an attached garage or enclosure or on an open utility platform that provides utility services for the building. Note that elevations for these specific machinery and equipment items are required in order to rate the building for flood insurance. Local floodplain management officials are required to ensure that <u>all</u> machinery and equipment servicing the building are protected from flooding. Thus, local officials may require that elevation information for all machinery and equipment, including ductwork, be documented on the Elevation Certificate. If the machinery and/or equipment is mounted to a wall, pile, etc., enter the platform elevation of the machinery and/

or equipment. Indicate machinery/equipment type and its general location, e.g., on floor inside garage or on platform affixed to exterior wall, in the Comments area of Section D or Section G, as appropriate. If this item does not apply to the building, enter "N/A" for not applicable.

**Items C2.f-g** Enter the elevation of the ground, sidewalk, or patio slab immediately next to the building. For Zone AO, use the natural grade elevation, if available. This measurement must be to the nearest tenth of a foot (nearest tenth of a meter, in Puerto Rico) if this certificate is being used to support a request for a LOMA or LOMR-F.

**Item C2.h** Enter the lowest grade elevation at the deck support or stairs. For Zone AO, use the natural grade elevation, if available. This measurement must be to the nearest tenth of a foot (nearest tenth of a meter, in Puerto Rico) if this certificate is being used to support a request for a LOMA or LOMR-F.

#### SECTION D – SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION

Complete as indicated. This section of the Elevation Certificate may be signed by only a land surveyor, engineer, or architect who is authorized by law to certify elevation information. Place your license number, your seal (as allowed by the State licensing board), your signature, and the date in the box in Section D. You are certifying that the information on this certificate represents your best efforts to interpret the data available and that you understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001. Use the Comments area of Section D, on the back of the certificate, to provide datum, elevation, openings, or other relevant information not specified on the front.

#### SECTION E – BUILDING ELEVATION INFORMATION (SURVEY NOT REQUIRED) FOR ZONE AO AND ZONE A (WITHOUT BFE)

Complete Section E if the building is located in Zone AO or Zone A (without BFE). Otherwise, complete Section C instead. Explain in the Section F Comments area if the measurement provided under Items E1–E4 is based on the "natural grade."

**Items E1.a and b** Enter in Item E1.a the height to the nearest tenth of a foot (tenth of a meter in Puerto Rico) of the top of the bottom floor (as indicated in the applicable diagram) above or below the highest adjacent grade (HAG). Enter in Item E1.b the height to the nearest tenth of a foot (tenth of a meter in Puerto Rico) of the top of the bottom floor (as indicated in the applicable diagram) above or below the highest adjacent grade (HAG). Enter in Item E1.b the height to the nearest tenth of a foot (tenth of a meter in Puerto Rico) of the top of the bottom floor (as indicated in the applicable diagram) above or below the lowest adjacent grade (LAG). For buildings in Zone AO, the community's floodplain management ordinance requires the lowest floor of the building be elevated above the highest adjacent grade at least as high as the depth number on the FIRM. Buildings in Zone A (without BFE) may qualify for a lower insurance rate if an engineered BFE is developed at the site.

**Item E2.** For Building Diagrams 6–9 with permanent flood openings (see pages 8–9), enter the height to the nearest tenth of a foot (tenth of a meter in Puerto Rico) of the next higher floor or elevated floor (as indicated in the applicable diagram) above or below the highest adjacent grade (HAG).

**Item E3.** Enter the height to the nearest tenth of a foot (tenth of a meter in Puerto Rico), in relation to the highest adjacent grade next to the building, for the top of attached garage slab. (Because elevation for top of attached garage slab is self-explanatory, attached garages are not illustrated in the diagrams.) If this item does not apply to the building, enter "N/A" for not applicable.

**Item E4.** Enter the height to the nearest tenth of a foot (tenth of a meter in Puerto Rico), in relation to the highest adjacent grade next to the building, of the platform elevation that supports the machinery and/or equipment servicing the building. Indicate machinery/equipment type in the Comments area of Section F. If this item does not apply to the building, enter "N/A" for not applicable.

**Item E5.** For those communities where this base flood depth is not available, the community will need to determine whether the top of the bottom floor is elevated in accordance with the community's floodplain management ordinance.

#### SECTION F – PROPERTY OWNER (OR OWNER'S REPRESENTATIVE) CERTIFICATION

Complete as indicated. This section is provided for certification of measurements taken by a property owner or property owner's representative when responding to Sections A, B, and E. The address entered in this section must be the actual mailing address of the property owner or property owner's representative who provided the information on the certificate.

#### SECTION G – COMMUNITY INFORMATION (OPTIONAL)

Complete as indicated. The community official who is authorized by law or ordinance to administer the community's floodplain management ordinance can complete Sections A, B, C (or E), and G of this Elevation Certificate. Section C may be filled in by the local official as provided in the instructions below for Item G1. If the authorized community official completes Sections C, E, or G, complete the appropriate item(s) and sign this section.

Check **Item G1** if Section C is completed with elevation data from other documentation, including elevations obtained from the Community Rating System Elevation Software, that has been signed and sealed by a licensed surveyor, engineer, or architect who is authorized by law to certify elevation information. Indicate the source of the elevation data and the date obtained in the Comments area of Section G. If you are both a community official and a licensed land surveyor, engineer, or architect authorized by law to certify elevation information, and you performed the actual survey for a building in Zones A1–A30, AE, AH, A (with BFE), VE, V1–V30, V (with BFE), AR, AR/A, AR/A1–A30, AR/AE, AR/AH, or AR/AO, you must also complete Section D.

Check **Item G2** if information is entered in Section E by the community for a building in Zone A (without a FEMA-issued or community-issued BFE) or Zone AO.

Check **Item G3** if the information in Items G4–G10 has been completed for community floodplain management purposes to document the as-built lowest floor elevation of the building. Section C of the Elevation Certificate records the elevation of various building components but does not determine the lowest floor of the building or whether the building, as constructed, complies with the community's floodplain management ordinance. This must be done by the community. Items G4–G10 provide a way to document these determinations.

**Item G4.** Permit Number. Enter the permit number or other identifier to key the Elevation Certificate to the permit issued for the building.

Item G5. Date Permit Issued. Enter the date the permit was issued for the building.

**Item G6.** Date Certificate of Compliance/Occupancy Issued. Enter the date that the Certificate of Compliance or Occupancy or similar written official documentation of as-built lowest floor elevation was issued by the community as evidence that all work authorized by the floodplain development permit has been completed in accordance with the community's floodplain management laws or ordinances.

**Item G7.** New Construction or Substantial Improvement. Check the applicable box. "Substantial Improvement" means any reconstruction, rehabilitation, addition, or other improvement of a building, the cost of which equals or exceeds 50 percent of the market value of the building before the start of construction of the improvement. The term includes buildings that have incurred substantial damage, regardless of the actual repair work performed.

**Item G8.** As-built lowest floor elevation. Enter the elevation of the lowest floor (including basement) when the construction of the building is completed and a final inspection has been made to confirm that the building is built in accordance with the permit, the approved plans, and the community's floodplain management laws or ordinances. Indicate the elevation datum used.

**Item G9.** BFE. Using the appropriate FIRM panel, FIS Profile, or other data source, locate the property and enter the BFE (or base flood depth) of the building site. Indicate the elevation datum used.


**Item G10.** Community's design flood elevation. Enter the elevation (including freeboard above the BFE) to which the community requires the lowest floor to be elevated. Indicate the elevation datum used.

Enter your name, title, and telephone number, and the name of the community. Sign and enter the date in the appropriate blanks.


# **Building Diagrams**

The following diagrams illustrate various types of buildings. Compare the features of the building being certified with the features shown in the diagrams and select the diagram most applicable. Enter the diagram number in Item A7, the square footage of crawlspace or enclosure(s) and the area of flood openings in square inches in Items A8.a–c, the square footage of attached garage and the area of flood openings in square inches in Items A9.a–c, and the elevations in Items C2.a–h.

In A zones, the floor elevation is taken at the top finished surface of the floor indicated; in V zones, the floor elevation is taken at the bottom of the lowest horizontal structural member (see drawing in instructions for Section C).



\* A floor that is below ground level (grade) on all sides is considered a basement even if the floor is used for living purposes, or as an office, garage, workshop, etc.




- \* A floor that is below ground level (grade) on all sides is considered a basement even if the floor is used for living purposes, or as an office, garage, workshop, etc.
- \*\* An "opening" is a permanent opening that allows for the free passage of water automatically in both directions without human intervention. Under the NFIP, a minimum of 2 openings is required for enclosures or crawlspaces. The openings shall provide a total net area of not less than 1 square inch for every square foot of area enclosed, excluding any bars, louvers, or other covers of the opening. Alternatively, an Individual Engineered Flood Openings Certification or an Evaluation Report issued by the International Code Council Evaluation Service (ICC ES) must be submitted to document that the design of the openings will allow for the automatic equalization of hydrostatic flood forces on exterior walls. A window, a door, or a garage door is not considered an opening; openings may be installed in doors. Openings shall be on at least 2 sides of the enclosed area. If a building has more than 1 enclosed area, each area must have openings to allow floodwater to directly enter. The bottom of the openings must be no higher than 1.0 foot above the higher of the exterior or interior grade or floor immediately below the opening. For more guidance on openings, see NFIP Technical Bulletin 1.

#### DIAGRAM 7

All buildings elevated on full-story foundation walls with a partially or fully enclosed area below the elevated floor. This includes walkout levels, where at least 1 side is at or above grade. The principal use of this building is located in the elevated floors of the building.


**Distinguishing Feature** – For all zones, the area below the elevated floor is enclosed, either partially or fully. In A Zones, the partially or fully enclosed area below the elevated floor is with or without openings\*\* present in the walls of the enclosure. Indicate information about enclosure size and openings in Section A – Property Information.



#### **DIAGRAM 8**

All buildings elevated on a crawlspace with the floor of the crawlspace at or above grade on at least 1 side, with or without an attached garage.


**Distinguishing Feature** – For all zones, the area below the first floor is enclosed by solid or partial perimeter walls. In all A zones, the crawlspace is with or without openings\*\* present in the walls of the crawlspace. Indicate information about crawlspace size and openings in Section A – Property Information.



#### DIAGRAM 9

All buildings (other than split-level) elevated on a sub-grade crawlspace, with or without attached garage.

**Distinguishing Feature** – The bottom (crawlspace) floor is below ground level (grade) on all sides.\* (If the distance from the crawlspace floor to the top of the next higher floor is more than 5 feet, or the crawlspace floor is more than 2 feet below the grade [LAG] on all sides, use Diagram 2.)



- \* A floor that is below ground level (grade) on all sides is considered a basement even if the floor is used for living purposes, or as an office, garage, workshop, etc.
- \*\* An "opening" is a permanent opening that allows for the free passage of water automatically in both directions without human intervention. Under the NFIP, a minimum of 2 openings is required for enclosures or crawlspaces. The openings shall provide a total net area of not less than 1 square inch for every square foot of area enclosed, excluding any bars, louvers, or other covers of the opening. Alternatively, an Individual Engineered Flood Openings Certification or an Evaluation Report issued by the International Code Council Evaluation Service (ICC ES) must be submitted to document that the design of the openings will allow for the automatic equalization of hydrostatic flood forces on exterior walls. A window, a door, or a garage door is not considered an opening; openings may be installed in doors. Openings shall be on at least 2 sides of the enclosed area. If a building has more than 1 enclosed area, each area must have openings to allow floodwater to directly enter. The bottom of the openings must be no higher than 1.0 foot above the higher of the exterior or interior grade or floor immediately below the opening. For more guidance on openings, see NFIP Technical Bulletin 1.

The floodproofing of non-residential buildings may be permitted as an alternative to elevating to or above the Base Flood Elevation; however, a floodproofing design certification is required. This form is to be used for that certification. Floodproofing of a residential building does not alter a community's floodplain management elevation requirements or affect the insurance rating unless the community has been issued an exception by FEMA to allow floodproofed residential basements. The permitting of a floodproofed residential basement requires a separate certification specifying that the design complies with the local floodplain management ordinance.

BUILDING OWNER'S NAME		
STREET ADDRESS (Including Apt., Unit, Suite, and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER		
OTHER DESCRIPTION (Lot and Block Numbers, etc.)		
CITY	STATE	ZIP CODE

#### SECTION I - FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Provide the following from the proper FIRM:							
COMMUNITY NUMBER	PANEL NUMBER	SUFFIX	DATE OF FIRM INDEX	FIRM ZONE	BASE FLOOD ELEVATION (In AO Zones, Use Depth)		
			_				

Indicate elevation datum used for Base Flood Elevation shown above: 🗌 NGVD 1929 🔲 NAVD 1988 🗌 Other/Source: \_

#### SECTION II – FLOODPROOFING INFORMATION (By a Registered Professional Engineer or Architect)

Elevations are based on: 🗌 Construction Drawings 📄 Building Under Construction 📄 Finished Construction						
Floodproofing Design Elevation Information:						
Building is floodproofed to an elevation of feet (In Puerto Rico only: meters). 🗌 NGVD 1929 🗍 NAVD 1988 🗍 Other/Source: (Elevation datum used must be the same as that used for the Base Flood Elevation.)						
Height of floodproofing on the building above the lowest adjacent grade is feet (In Puerto Rico only: meters).						
For Unnumbered A Zones Only:						
Highest adjacent (finished) grade next to the building (HAG) feet (In Puerto Rico only: neters)						
□ NGVD 1929 □ NAVD 1988 □ Other/Source:						
(NOTE: For insurance rating purposes, the building's floodproofed design elevation must be at least 1 foot above the Base Flood Elevation to receive rating credit. If the building is floodproofed only to the Base Flood Elevation, then the building's insurance rating will result in a higher premium.)						

#### SECTION III – CERTIFICATION (By a Registered Professional Engineer or Architect)

#### Non-Residential Floodproofed Construction Certification:

I certify that, based upon development and/or review of structural design, specifications, and plans for construction, the design and methods of construction are in accordance with accepted standards of practice for meeting the following provisions:

The structure, together with attendant utilities and sanitary facilities, is watertight to the floodproofed design elevation indicated above, with walls that are substantially impermeable to the passage of water.

All structural components are capable of resisting hydrostatic and hydrodynamic flood forces, including the effects of buoyancy, and anticipated debris impact forces.

I certify that the information on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME	LICENSE NUMBER (or Affi:	LICENSE NUMBER (or Affix Seal)			
TITLE	COMPANY NAME	COMPANY NAME			
ADDRESS	CITY	STATE	ZIP CODE		
SIGNATURE	DATE	PHONE			

Copies should be made of this Certificate for: 1) community official, 2) Insurance agent/company, and 3) building owner.

# FLOODPROOFING CERTIFICATE

### FOR NON-RESIDENTIAL STRUCTURES

#### **Paperwork Reduction Act Notice**

**General:** This information is provided pursuant to Public Law 96-511 (the Paperwork Reduction Act of 1980, as amended), dated December 11, 1980, to allow the public to participate more fully and meaningfully in the Federal paperwork review process.

Authority: Public Law 96-511, amended; 44 U.S.C. 3507; and 5 CFR 1320.

**Paperwork Burden Disclosure Notice:** Public reporting burden for this data collection is estimated to average 3.25 hours per response. The burden estimate includes the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and submitting this form. You are not required to respond to this collection of information unless a valid OMB control number is displayed on this form. Send comments regarding the accuracy of the burden estimate and any suggestions for reducing the burden to: Information Collections Management, Department of Homeland Security, Federal Emergency Management Agency, 1800 South Bell Street, Arlington, VA 20598-3005, Paperwork Reduction Project (1660-0008). **NOTE: Do not send your completed form to this address.** 

#### **Privacy Act Statement**

Authority: Title 44 CFR § 61.7 and 61.8.

**Principal Purpose(s):** This information is being collected for the primary purpose of estimate the risk premium rates necessary to provide flood insurance for new or substantially improved structures in designated Special Flood Hazard Areas.

**Routine Use(s):** The information on this form may be disclosed as generally permitted under 5 U.S.C. § 552a(b) of the Privacy Act of 1974, as amended. This includes using this information as necessary and authorized by the routine uses published in DHS/FEMA-003 – National Flood Insurance Program Files System or Records Notice 73 Fed. Reg. 77747 (December 19, 2008); DHS/FEMA/NFIP/LOMA-1 – National Flood Insurance Program (NFIP) Letter of Map Amendment (LOMA) System of Records Notice 71 Fed. Reg. 7990 (February 15, 2006); and upon written request, written consent, by agreement, or as required by law.

**Disclosure:** The disclosure of information on this form is voluntary; however, failure to provide the information requested may result in the inability to obtain flood insurance through the National Flood Insurance Program or may be subject to higher premium rates for flood insurance. Information will only be released as permitted by law.